



colour  
touch-screen  
with  
force-time  
curve

# **EPT 1000**

## **Pull Tester**

- Touch-screen
- User-friendly menu navigation
- Ergonomic clamp arrangement
- Variable-speed motor for constant pull-speed
- Variable pull speeds 25, 50 & 100 mm/min
- Extra-long displacement path
- Destructive & non-destructive tests
- USB interface
- SD card slot




Quality control

[www.smcontact.eu](http://www.smcontact.eu)


## Ergonomic use of the device

The ELPAC EPT 1000 pull tester is a **brand-new motorized tester** for measurement of the pull forces in crimp connections and peeling forces in welding joints. The device has a measurement range of up to 1000 N. The measured values can be displayed in N, kgf and lbf. A speed-controlled motor guarantees **a constant pull speed**. There are three pull speed settings: 25, 50 and 100 mm/min.

The horizontal holder arrangement guarantees **ergonomic use of the device**. The samples are held in a rotating interchangeable holder, supplied as standard. Simple rotation of the holder enables use of the adapter with 12 different slot widths or of the clamp. Therefore the unit can be used for practically all required cable processing tests (standard IEC 60352-2).



## 65.536-colour touch-screen



The straightforward design of the user interface with a **colour touch-screen** and **intuitive menu navigation** simplifies operation and enables reproducible test results. The **force-time characteristic** is displayed as a **curve on the screen**. The measured values can be saved to an SD card and retrieved later. This also enables statistical analyses to be carried out on the device.

The EPT 1000 pull tester can be connected via an existing USB interface.



## Technical data

Measurement range:	0 - 1000 N
Measurement unit:	N, kgf, lbf
Display:	65.536-colour touch-screen
Sensor accuracy:	1% from end of measurement range
Operating temperature:	0 - 40° C
Max. displacement:	157 mm
Speed control:	variable, 3 speeds 25, 50 und 100 mm/min
Pull methods:	<ul style="list-style-type: none"> <li>Pull and pull-off (destructive)</li> <li>Pull and hold up to a defined force and duration</li> <li>Pull and release up to a defined force</li> <li>Pull and hold at defined force and duration, then pull off</li> </ul>
Measure value storage device:	SD-card (up to 32 GB)
Graphical display:	force-time curve on screen
Ingress protection:	IP 20
Interfaces:	USB
Power supply:	230 V/AC
Weight:	11,5 kg
Dimensions (WxDxH):	450 x 185 x 170 mm
CE-conformity:	Device conforms fully to CE- and EMC machinery directives

SPARE PARTS  
ON  
TOOLING.SMCONTACT.EU

### SM CONTACT GMBH

D-66113 Saarbrücken  
 Germany  
 Lebacher Str., 4  
 Tel.: +49 (0) 9127 9536714  
 sales\_de@smcontact.eu

### SM CONTACT ENGINEERING

196191 Saint-Petersburg  
 Russia  
 21-A, Basseynaya Str.  
 Tel.: +7 812 980 97 93  
 info@smcontact.ru

### SM CONTACT ASIA

555 Panyu RD • GuangZhou Chi-  
 na • 205 Exchange Center TianAn  
 Hi-tech Ecological park  
 Tel.: +86 (0)20 22883182  
 info@smcontact.cn

# EPT 1000 on YouTube

