




Phone: +39 049 7641230 - Fax: +39 049 9344179 info@kmcorporate.com - www.kmcorporate.com





The safety guards can be completely opened to allow an easy access to the working area and a simple and fast miniapplicator changeover. The reel holder bracket allows a simple and quick shift of the terminal feeding sense.

The standard feature includes the footswitch for the cycle drive, a transparent shock-proof safety guards for a full view of the working area and the lamp for the working area lighting.

On request the machine can be equipped with a crimp force monitor system, quick coupling base for clamping of the miniapplicator and a kit for use of pneumatic miniapplicators.





Revolving reel support bracket

	KN 21M	
Crimping force	20kN (2 ton)	
Power supply	230V - 50/60 Hz	
Power consumption	1,8 Kw (8A)	
Noise level	< 80Db(A)	
Standard stroke, mm	40 mm	
Lower dead center, mm	min 132 - max 137 mm	
Wire cross-section	up to 6 mm. (AWG 10)	
Cycles/h	5000	
Weight, kg	540 N ( 55 Kg)	
Weight with packing	640 N (65 Kg)	
Dimensions without coil holders	mm 340 x 435 x 710 h	
Dimensions with packing	mm 800 x 600 x 1040 h	

Optional Crimping force monitor - Quick base kit - Pneumatic kit

All data and measures are indicative and can be changed without notice. Certain types of extremely hard, tough wires may not be able to be processed even if written within the indicated ranges. In case of doubt, KM Corporate is willing to produce samples of your wire.