



Via delle Prese, 16/18 – 36015 SCHIO (VI)
 Tel. 0445. 576115 – fax. 0445.575931 Assistenza Tecnica : Tel. 0445. 576149 – Fax. 0445. 501255
 e-mail: macchine@samecitaly.it – web site: <http://www.samecitaly.it>

WIRE CUTTING AND STRIPPING MACHINE

MOD. SAMEC TSS-100A - TSS-2TA – TSS-100AP – TSS-2TAP



Wire cutting and stripping machine	Mod. TSS-100A Mod. TSS-2TA - 2 heads	Mod. TSS-100AP Mod. TSS-2TAP – 2 heads With servomotor and positioned cut
Safety guards	In accordance with CE standards	
Data set up	By keyboard and back lighted display	
Programmable quantity of pieces	max. 9.999	
Storable customer quantity	max. 50	
Storable cable quantity per customer	max. 20	
Quantity of batches:	programmable	
Workable length:	Min. 45 mm. – max. 100 mt.	Min. 45 mm. – max. 500 mt.
Machine hole:	mm. 10 x 10	
Workable outer diameter	min. 0,5 mm. – max. 9 mm.	
Max. cross section (multiconductor stranded cable)	15 mm ²	
Insulator displaceable length:	max. 20 mm.	
Single wire stripping length:	min. 3 mm.	
Total stripping length:	100 mm. – mod. TSS-100A 230 mm. – mod. TSS-2TA	100 mm. – mod. TSS-100AP 230 mm. – mod. TSS-2TAP
Short end jacket stripping length:	/	/ – TSS-100AP Max. 110 mm. - TSS-2TAP
Opposite end stripping length:	/	/ – TSS-100AP Max. 9 mt. – TSS-2TAP
Acceleration and deceleration ramps:	/	
Cable speed:	max. 2 mt./sec.	
Machine pre-arranged for line connection with:	pre-feeder or pay off, marking machine, linear collector , coiler	
Power supply:	220/230V 50/60 Hz.	
Air supply	6-8 bar continuos	
Max absorbed power:	500W	1 KW